

N O T I C E

THIS DOCUMENT HAS BEEN REPRODUCED FROM
MICROFICHE. ALTHOUGH IT IS RECOGNIZED THAT
CERTAIN PORTIONS ARE ILLEGIBLE, IT IS BEING RELEASED
IN THE INTEREST OF MAKING AVAILABLE AS MUCH
INFORMATION AS POSSIBLE

NASA Technical Memorandum 81568

(NASA-TM-81568) TOWARD THE USE OF
SIMILARITY THEORY IN TWO-PHASE CHOKED FLOWS
(NASA) 12 p HC A02/MF A01 CSCL 20D

N80-29623

Unclass

G3/34 28456

TOWARD THE USE OF SIMILARITY THEORY IN TWO-PHASE CHOKED FLOWS


R. C. Hendricks
Lewis Research Center
and

J. V. Sengers
University of Maryland
College Park, Maryland
and

R. J. Simoneau
Lewis Research Center
Cleveland, Ohio

Prepared for the
Winter Annual Meeting of the American
Society of Mechanical Engineers
Chicago, Illinois, November 16-21, 1980

NASA



TOWARD THE USE OF SIMILARITY THEORY IN TWO-PHASE CHOKED FLOWS

R. C. Hendricks, J. V. Sengers*, and R. J. Simoneau

**NASA Lewis Research Center
Cleveland, Ohio 44135**

and

***University of Maryland
College Park, Maryland**

ABSTRACT

Comparison of two-phase choked flows in normalized coordinates were made between pure components and available data using a reference fluid to compute the thermophysical properties. The results are favorable. Solution of the governing equations for two LNG mixtures show some possible similarities between the normalized choked flows of the two mixtures, but the departures from the pure component loci are significant.

NOMENCLATURE

a_{1-5}	constants, eq. (11)
b_{1-4}	constants, eq. (12)
G	mass flux ($G = \rho U$)
G^*	mass flux normalizing parameter ($\sqrt{P_c \rho_c / Z_c}$)
G_o^*	$(\sqrt{f}/h)G_o^*$ for corresponding states with reference fluid (0) and working fluid (α)
g	configurational free energy
h	scaling function - volume
f	scaling function - temperature
m	molecular weight
P	pressure
R	gas constant
S	entropy
T	temperature
U	fluid velocity
V	specific volume
x	mole fraction
Z	compressibility

Greek:

ρ	density
n, δ	binary interaction parameter
ϕ, ϕ	configuration function
ω	Pitzer's eccentric factor
z	property parameter

Subscripts:

c	critical
e	exit
α	fluid- α
ij	fluid i - fluid j
o	reference fluid
m	mixture
t	throat
R	reduced

Superscript:

c	critical
-----	----------

INTRODUCTION

Using conventional corresponding states techniques, we have found normalizing parameters which can be applied in two-phase choked flow computations (refs. 1 to 4). The pure component properties of the working fluid, along with the flow equations, are used to define the critical mass flux and pressure ratio profiles. When compared to available experimental data the agreement was good (refs. 4 and 5).

Although the normalized charts are applicable to a wide variety of simple fluids, it has not been demonstrated, via direct calculation, that a reference fluid (0) can be used to predict the proper-

ties of another fluid (a) in conjunction with calculations of two-phased choked flow parameters for fluid (a) using fluid (0); the pure-pure problem.

Further, the application of these parameters to fluid mixtures and the problems associated with the computation of two-phase choked flows of mixtures has not been treated using the one fluid van der Waals approximation (refs. 6 to 11) for predicting thermophysical properties; the pure-mix problem.

In this paper, we wish to address both the pure-pure and the pure-mix problems in two-phase choked flows using the thermophysical properties codes of references 12 and 10, respectively. It is important to study the fluid mechanics of mixtures as most working fluids are mixtures of varying composition.

GOVERNING EQUATIONS

The equations governing homogeneous equilibrium two-phase choked flows are detailed in references 2 and 4. The mass flux is given as equation (1):

$$G^2 = \frac{2}{V^2} \int_p^p V dp \quad (1)$$

Constraints:

$$G^2 \left(\frac{dV}{dp} \right)_e = 1 \quad (2)$$

$$S(P_0, T_0) = \text{constant} \quad (3)$$

The solution of equation (1) is easy enough if V is known. The whole problem lies in computing V subject to constraints 2 and 3. For the simplified pure-pure problem, this is rather straightforward using a thermophysical properties package such as GASP (ref. 12), but can become complex for the pure-mix problem, depending on mixture composition.

In this paper, a reference fluid (0) will be used to determine the thermophysical properties necessary to satisfy equations (1), (2), and (3) for both the pure-pure and the pure-mix problems. The mixture equations, detailed by Mollerup (refs. 7 to 10), are given here in abridged form where Z is the compressibility function, g the configurational Gibbs free energy, and x_j the mole fraction of component j .

$$Z_m(V, T, x_j) = Z_0(V/h, T/f) \quad (4)$$

$$g_m(V, T, x_j) = fg_0(V/h, T/f)$$

$$+ RT \left(\sum_j x_j \ln x_j - \ln h \right) \quad (5)$$

where the scaling functions, f and h are defined as:

$$h = \sum_i \sum_j x_i x_j h_{ij} \quad (6)$$

$$fh = \sum_i \sum_j x_i x_j h_{ij} f_{ij} \quad (7)$$

and the interaction parameters h_{ij} and f_{ij} are

defined in terms of assumed mixing rules and critical parameters relating component- k to the reference fluid (0):

$$f_{ij} = n_{ij}(f_{ij}, f_{jj})^{1/2} \quad (8)$$

$$h_{ij} = \phi_{ij} \left(\frac{h_{ii}^{1/3} + h_{jj}^{1/3}}{2} \right)^3 \quad (9)$$

$$f_{ii} = \left(\frac{T_i}{T_0} \right) \phi; h_{ii} = \left(\frac{V_i}{V_0} \right) \phi \quad (10)$$

with binary interaction parameters n_{ij} and ϕ_{ij} . Configuration functions ϕ and ϕ are slowly varying functions of V_R and T_R and can be defined in a variety of ways. The most successful are the Leach-Leyland forms (ref. 6), or their modifications such as given by Mollerup (ref. 10) and McCarty (ref. 11)

$$\phi = 1 + (\omega_i - \omega_0)[a_1(V_R - a_2) - a_3(V_R - a_4)] \ln T_R \quad (11)$$

$$\frac{Z_0}{Z_i} \phi = 1 + (\omega_i - \omega_0) \left[b_1 - b_2 \ln T_k + \left(b_3 - \frac{b_4}{T_R} \right) (V_R - b_5) \right] \quad (12)$$

The coefficients a_j and b_j are estimated from experimental data (refs. 10 and 11).

For the pure-pure problem, equations (4) to (10) are simplified since the crossterms do not enter; for example, with only one component, equations (5) to (7) become:

$$g(V, T, 1) = fg_0(V/h, T/f) - RT \ln h \quad (13)$$

$$h = \left(\frac{T_i}{T_0} \right) \phi \quad (14)$$

$$f = \left(\frac{V_i}{V_0} \right) \phi \quad (15)$$

For the derivatives necessary to solve the governing equations, see Mollerup (ref. 10).

RESULTS

The pure-pure problem results are presented first since they are direct and readily explained in terms of data. By contrast, the pure-mix problem which is complex, is further complicated by lack of data.

Pure-Pure

Using the thermophysical property codes of reference 12, the governing equations were solved for pure components nitrogen and oxygen on three selected isotherms for which accurate experimental data are available. Subsequent verification checks were made using the Mollerup code, (ref. 10), with simi-

lar results; the exception being near the saturation locus where some discrepancies noted.

In figures 1(a) and (b) the calculated critical mass flux and pressure ratio profiles in normalized coordinates are compared to experimental data. The curve labeled $\text{CH}_4 - \text{N}_2$ was calculated using the properties of methane; that is, fluid (0) is methane and fluid (a) is nitrogen; similarly, for the curve marked $\text{CH}_4 - \text{O}_2$. The use of nitrogen or oxygen as the reference fluid did not alter the results of figures 1 to 3. The agreement with data is quite good, and similar departures from a single curve were found when using fluid nitrogen or fluid oxygen properties directly.

Approaching the critical isotherm, while the mass flux agreement is good, figure 2(a), a rather large and as yet unexplained departure in the pressure profiles between data and theory can be noted, figure 2(b).

Close to the critical isotherm, the agreement with data is again good, as noted in figures 3(a) and (b).

It must be pointed out that the fluid nitrogen and fluid oxygen data are in very good agreement. The discrepancies lie in the governing equations, and their solutions.

Pure-Mix

Some initial computations using the governing equations and the more conventional corresponding states approach to defining the normalizing parameters appeared successful. But a closer examination revealed several problems and the approach was abandoned. Calculations for two mixtures are presented as a method of comparison.

Conventional corresponding states techniques, some of which are given in reference 13, cannot be applied to mixtures with any degree of confidence. The linear molar fraction method:

$$z^C = \sum_i z_i^C x_i \quad (16)$$

$$p^C = z^C R T^C / V^C \quad (17)$$

where z^C represents a property, is simple to apply but not reliable and the complex techniques recommended by reference 14 are better.

With the molar fractions of mixtures Mix_1 and Mix_2 given in tables I and II, some estimates of the critical parameters can be made which then can be compared to those estimated using Mollerup's program (ref. 10). The results are given in tables I and II to illustrate the point. Further, the circondenbar (maximum pressure) and circondentherm (maximum temperature) are given for each mixture. For all calculations the reference fluid is methane.

The nature of the vapor pressure locus at a fixed composition is given as figure 4 for mixtures Mix_1 and Mix_2 , respectively. While alike in general appearance, the critical point of Mix_2 is close to the circondenbar. Further note that at temperatures greater than critical, following an isotherm from the high-pressure gas side with decreasing pressure, condensation first occurs on the dew line and attains a maximum density followed by an evaporation at the dew line again, and returns to the low pressure gas state. The composition of the fluid changes, as illustrated in figure 5 for the major components of Mix_1 . At lower pressures, the

liquid is dominated by the least volatile components n-heptane and hexane. Finally, a temperature entropy diagram, figure 6, for Mix_1 can be used to "spot" and follow the expansion process. Note that expansions occurring between 190 and 400 K, depending on pressure, terminate at about the saturation locus near the critical point to the circondentherm; that is, the region most difficult to handle and which is the one of most interest.

With this behavior, it should not be too surprising that we have significant difficulties in computing the critical mass flux for Mix_1 and Mix_2 .

The critical mass flux for Mix_1 in normalized coordinates is presented in figure 7 with the conventional pure-pure normalized loci, as background. There are rather significant differences: (1) the saturation locus, (2) the slopes of the isotherms, and (3) regions where computations are incomplete; the exception being the gaseous phase where similar behavior is noted. In many computational attempts, no reasonable solution was found as illustrated by the 1.1 reduced isotherm and the regions previously cited from the near-critical to the circondentherm. These difficulties will require a reassessment of the governing equations.

As a further comparison, the solution of the governing equations for a second similar mixture (both LNG), Mix_2 was carried out. The results are given in normalized coordinates in figure 8. Comparing the results for Mix_1 and Mix_2 indicates two possible similarities: (1) the slopes of the isotherms and (2) the saturation loci are in better agreement than with the pure-pure background curves. Figure 9 gives a more direct comparison between Mix_1 and Mix_2 and corresponding states. The G^* values for Mix_1 and Mix_2 were calculated using reference 13. At this time it does not appear reasonable to expect these curves to "collapse" to representative isotherms as composition dependence significantly alters the behavior near the saturation locus. Experimental two-phase choked flow data for fluid mixtures are indispensable.

SUMMARY

For the pure-pure problem involving fluids of simple (non-quantum) molecular structure, the conventional corresponding states approach to computations of two-phase choked flows appears valid. The use of the van der Waals one fluid model and a computer program such as Mollerup (ref. 10), with the appropriate reference fluid also appears to be a valid approach.

The departures of two-phase choked flows in normalized coordinates for the pure-pure and the pure-mix problems are significant and composition dependent.

For the mixture, the critical parameters, circondenbar and circondentherm need to be determined from the governing equations or experimental data. Once found, some normalization may be effective in grouping data as it becomes available.

REFERENCES

1. Hendricks, R. C.: Normalizing Parameters for the Critical Flow Rate of Simple Fluids Through Nozzles. K. Mendelssohn, Ed. 5th Int. Cryogenic Engr. Conf., IPC Science and Tech., Press, 1974, pp. 278-281.
2. Simoneau, R. J.; and Hendricks, R. C.: Generalized Charts for Computations of Two-Phased

- Choked Flow of Simple Cryogenic Liquids. Cryogenics, vol. 17, 1977, pp. 73-76.
3. Hendricks, R. C.; and Sengers, J. V.: Application of the Principle of Similarity to Fluid Mechanics. NASA TM X-79258, 1979.
 4. Simoneau, R.; and Hendricks, R. C.: Two-Phase Choked Flow Cryogenic Fluids in Converging-Diverging Nozzles. NASA TP-1484, 1979.
 5. Hendricks, R. C.; Simoneau, R. J.; and Barrows, R. F.: Two-Phased Choked Flow of Subcooled Oxygen and Nitrogen. NASA TN D-8169, 1976.
 6. Leach, J. W.: Molecular Structure Correction for Applying the Theory of Corresponding States to Non-Spherical Pure Fluids and Mixtures. Ph.D. Thesis, Rice University, Houston, Texas, 1967.
 7. Mollerup, J.: Thermodynamic Properties of Natural Gas, Petroleum Gas and Related Mixtures: Enthalpy Predictions. Advances in Cryogenic Engr., K. D. Timmerhaus, ed., vol. 23, 1977, pp. 550-560.
 8. Mollerup, J.: Thermodynamic Properties from Corresponding States Theory. AIChE Paper 456, 1978.
 9. Mollerup, J.: Correlated and Predicted Properties of LNG and Related Mixtures in the Normal and Critical Regimes. Advances in Cryogenic Engr., K. D. Timmerhaus, ed., vol. 20, 1975, pp. 172-194.
 10. Mollerup, J.: General Computer Programmer for Calculation of Thermodynamic Properties of Natural Gas and Petroleum Gas Mixtures. Vol. 1. Theory, Documentation, Sample Runs and Programme Description. Institutet for Kemi-teknik, Denmarks Tekniske Højskole, Lyngby, Denmark, 1979.
 11. McCarty, R. D.: A Comparison of Mathematical Models for the Prediction of LNG Densities., NBS IR 77-867, 1977.
 12. Hendricks, R. C.; Baron, A. K.; and Feller, I. C.: GASP - A Computer Code for Calculating the Thermodynamic and Transport Properties for Ten Fluids: Parahydrogen, Helium, Neon, Methane, Nitrogen, Carbon Monoxide, Oxygen, Fluorine, Argon, and Carbon Dioxide, NASA TN D-7818, 1975. Based in part on the work of: Bender, E.: Equation of State Exactly Representing the Phase Behavior of Pure Substances. Proceedings of the Fifth Symposium on Thermophysical Properties. ASME, 1971, pp. 227-235.
 13. Reid, R. C.; Prausnitz, J. M.; and Sherwood, T. K.: The Properties of Gases and Liquids. McGraw-Hill Book Co., Inc., 3rd Ed., 1977.

TABLE I. - MIXTURE COMPOSITION, NORMALIZING AND CRITICAL PARAMETERS FOR MIX₁

Composition-Mole Fraction

1. Methane	0.9718	5. n-Butane	0.0048	9. Heptane	0.0036
2. Ethane	0.0477	6. 1-Pentane	0.0013	10. Nitrogen	0.026
3. Propane	0.017	7. n-Pentane	0.001	11. Carbon dioxide	0.01
4. 1-Butane	0.0028	8. Hexane	0.001		

Method	P _c , MPa	T _c , K	V _c , cc/g	Z _c	m, g/g-mole	G*, g/cm ² -sec	Circondenbar, MPa	Circondenthm., K
Eq. (16)	4.6	202.7	5.79	0.285	18.02	5280	----	-----
Ref. 13	6.21	213.0	5.3	0.335	18.02	5915	----	-----
Mollerup code (ref. 10)	6.46	212.0	4.26	0.281	18.02	7340	8.45	267.4

TABLE II. - MIXTURE COMPOSITION, NORMALIZING AND CRITICAL PARAMETERS FOR MIX₂

Composition-Mole Fraction

1. Methane	0.6975	3. Propane	0.092	5. n-Butane	0.029
2. Ethane	0.156	4. 1-Butane	0.014	6. Nitrogen	0.0115

Method	P _c , MPa	T _c , K	V _c , cc/g	Z _c	m, g/g-mole	G*, g/cm ² -sec	Circondenbar, MPa	Circondenthm., K
Eq. (16)	4.53	234.0	5.36	0.284	22.75	5455	---	-----
Ref. 13	8.95	261.0	4.39	0.411	22.75	7040	---	-----
Mollerup code (ref. 10)	8.9	243.0	3.09	0.309	22.75	9650	9.2	299.0

$G^* = \sqrt{P_c \rho_c / Z_c}$ and $G_a^* = \sqrt{f/h} G_0^*$ for corresponding states applications with reference fluid (0) and working fluid (a) nearly equivalent for these fluids.





Figure 1 - Choked flow rate and pressure ratio as a function of reduced pressure for a reduced temperature of 0.749 - conical nozzle.







Figure 2 - Choked flow rate and pressure ratio as a function of reduced pressure for a reduced temperature of 0.942 - conical nozzle.

○ OXYGEN
□ NITROGEN



(a) Choked flow rate.



(b) Pressure ratio.

Figure 3 - Choked flow rate and pressure ratio as a function of reduced pressure for a reduced temperature of 1.025 - conical nozzle.




Figure 4 - Vapor pressure loci for mixtures Mix₁ and Mix₂. See Tables I and II for composition.




Figure 5. - Primary mole fractions - pressure loci at saturation conditions for mixture Mix₁. See Table I for complete composition array.




Figure 6. - Temperature - entropy chart for mixture Mix₁. See Table I for composition.




Figure 7. - Reduced critical mass flux as a function of reduced inlet stagnation temperature for selected isotherms for mixture Mix₁ with conventional corresponding states locii as background.




Figure 8. - Reduced critical mass flux as a function of reduced inlet stagnation pressure for selected isotherms for mixture Mix₂.




Figure 9. - A comparison of reduced critical mass flux as a function of reduced inlet stagnation pressure for selected isotherms for Mix_1 , Mix_2 , and corresponding states using G^* Tables I, II, ref. 13.

1 Report No NASA TM-81588	2 Government Accession No	3 Recipient's Catalog No
4 Title and Subtitle TOWARD THE USE OF SIMILARITY THEORY IN TWO PHASE CHOKED FLOWS	5 Report Date	6 Performing Organization Code
7 Author(s) R. C. Hendricks, J. V. Sengers[†], and R. J. Simoneau	8 Performing Organization Report No E-533	10 Work Unit No
9 Performing Organization Name and Address National Aeronautics and Space Administration Lewis Research Center Cleveland, Ohio 44135	11 Contract or Grant No	13 Type of Report and Period Covered Technical Memorandum
12 Sponsoring Agency Name and Address National Aeronautics and Space Administration Washington, D.C. 20546	14 Sponsoring Agency Code	
15 Supplementary Notes [†]University of Maryland, College Park, Maryland. Prepared for the Winter Annual Meeting of the American Society of Mechanical Engineers, Chicago, Illinois, November 16-21, 1980.		
16 Abstract Comparison of two-phase choked flows in normalized coordinates were made between pure components and available data using a reference fluid to compute the thermophysical properties. The results are favorable. Solution of the governing equations for two LNG mixtures show some possible similarities between the normalized choked flows of the two mixtures, but the departures from the pure component loci are significant.		
17 Key Words (Suggested by Author(s)) Choked flow Two phased flow Similarity Mixtures	18 Distribution Statement Unclassified - unlimited STAR Category 34	
19 Security Classif. (of this report) Unclassified	20 Security Classif. (of this page) Unclassified	21 No. of Pages 11
		22 Price* A02

* For sale by the National Technical Information Service, Springfield, Virginia 22161